Internal solid wall insulation Adding a thermal layer to the inside walls





Cut-away model of internal solid wall insulation.

1 | Surface coating

This is the new plasterwork that covers the insulation layer. Just like a normal internal wall, it can be painted (green in this case) or papered

2 | Insulation

This is the layer that prevents warmth escaping through the outside walls of the house. In this case, rigid insulation boards have been used.

3 | Internal wall

This is the old internal plaster which is now covered by the new insulation board and plasterwork.

4 | Windows

Ideally, the insulation board is fitted to the inside of the window recess to prevent cold patches developing where condensation forms. But, as is the case here, this is not always possible.

5 | External wall

From the outside your property will look exactly the same.

Nearly half of all the heat lost from some solid-walled houses escapes through the walls. Insulating these walls will slow down the rate of heat loss and keep the warmth inside the home for longer.

Solid wall insulation may be suitable for a variety of property types such as brick, stone, steel-framed and concrete construction.

Internal solid wall insulation works by adding a thermal layer of material to the existing wall. Solid walls can be insulated internally (from the inside) and externally (from the outside). Both are significant undertakings in terms of cost and disruption but both options can make your home warmer and greatly reduce your heating bills at the same time.

Internally insulating your walls will reduce the size of your rooms. However you may find that by making a cold wall warmer they actually increase the amount of usable space.

How do I know if my home has solid walls?

If your home is made of brick, and the bricks have an alternating long-short-long pattern, then the walls are likely to be solid. If you can see only the long edge of the bricks, then the wall is almost certainly a cavity construction.



Internal solid wall insulation is particularly appropriate where you need to keep the outside of your home looking the same



If the brick work is not visible then measuring the thickness of the wall at any entrance or window will help to determine the construction type. A solid brick wall is usually about 22cm thick, a cavity wall between 27cm and 30cm and a solid stone wall as much as 50cm thick. The age of your home can also be a good indicator; if it was built before the late 1920s it is likely to have solid walls.

Types of internal solid wall insulation

There are various ways to insulate a solid walled building from within, but they broadly fall into three categories:

1) Rigid insulation boards

These come in a variety of materials and thicknesses and deliver the highest energy saving. Some have pre-attached plasterboard which makes the installation process more straightforward.

2) Dry lining

Battens are fixed to the walls, insulation is fitted between them and then covered with plasterboard. This is a good option if the wall has a lot of heavy fittings such as book cases or kitchen cupboards, or if the original wall is rough and uneven, as in some stone properties.

3) Flexible thermal lining

This comes in rolls like thick wallpaper and is glued to the wall using a special adhesive. Flexible linings may not



Eden Rural Foyer, Old London Road Penrith CA11 8ET

01768 210276 www.cafs.org.uk office@cafs.org.uk

Facebook **/CAfSonline** Twitter @**CAfStweets**

Charity Number: 1123155 Registered Company Number: 06492907 provide the same level of insulation but you could install the material yourself if you are a competent DIYer. Moreover, as flexible linings tend to be no more than 10mm thick they can be a good option for rooms that have limited space.

Average cost and savings

Internally insulating your home will probably cost between £5,500 and £8,500, depending on how many rooms are being renovated and the type of material being used. Generally this is less expensive than external solid wall insulation because of the lower cost of materials and labour. A typical 3-bedroom semi-detached house using gas heating could save around £260 per year on heating bills by installing internal wall insulation whereas a detached house heating with oil could save around £450 per year.

Disruption

Internal solid wall insulation is a significant undertaking that inevitably involves a degree of disruption. Your installer should make you aware of any particular issues but things to consider include:

- A skip may be required;
- Rooms where the work is being done may not be usable whilst the work is being carried out and furniture, kitchen units etc may need to be temporarily removed;
- Fittings such as radiators, skirting boards, window sills and plug sockets on the wall that is being insulated will need to be removed and reattached afterwards;
- Pipe work and wiring may need to be re-laid;
- The works will produce dust and could well be noisy;
- Contractors will require water and power and the use of a toilet;
- The newly insulated walls and adjacent surfaces will need to be re-decorated when the work has finished.



This leaflet was originally produced by the Centre for Sustainable Energy, a national charity (no. 298740) that helps people change the way they think and act on energy | www.cse.org.uk

Cumbria Action for Sustainability (CAfS)

work to promote low carbon living, energy saving and reduced use of fossil fuels throughout Cumbria; we provide information, advice and motivation through events, site visits and practical projects.

Contact us for more information of our energy advice events and workshops and how we can help you save energy in your home.

